



Holdfast was engineered with one key goal in mind: GRIP. This rope utilizes HMPE and Nylon fibers to deliver a lightweight, high-strength, floating line that will grip on H-bitts and capstans much better than traditional 100% HMPE lines. Holdfast is coated with TEUFELBERGER's proprietary abrasion resistant coating that is specially formulated to yield higher strength and more durable and water-resistant lines. Coatings are available in assorted colors.

Applications

- Barge Line
- H-bitt Working Line
- Tug Pendant
- Tug Winch Line
- Winch Line
- Capstan Line
- Dry Docks
- General Purpose Working Line



Diameter		Circumference	Weight		Min. Breaking Strength	Avg. Breaking Strength
[inch]	[mm]		[inch]	[lbs/100']		
3/4	18	2 1/4	14.76	219.6	35,010	38,900
7/8	22	2 3/4	18.05	268.5	44,730	49,700
1	24	3	21.62	321.7	55,800	62,000
1 1/8	28	3 1/2	30.93	460.2	69,750	77,500
1 1/4	30	3 3/4	33.84	503.5	79,020	87,800
1 5/16	32	4	38.54	573.4	92,250	102,500
1 3/8	34	4 1/8	43.43	646.2	97,650	108,500
1 1/2	36	4 1/2	46.91	697.9	110,070	122,300
1 5/8	40	5	58.84	875.4	131,400	146,000
1 3/4	44	5 1/2	66.65	991.6	152,550	169,500
2	48	6	79.15	1,177.6	176,850	196,500
2 1/4	56	7	113.27	1,685.2	247,950	275,500
2 1/2	60	7 1/2	133.39	1,984.6	278,100	309,000
2 5/8	64	8	160.93	2,394.3	325,800	362,000
3	72	9	210.84	3,136.9	417,600	464,000

CM_DS_Hold_03A_1