



Note: Capacities and weights are listed in pounds.
Metric load chart is available upon request and sling lengths can be made in either feet or meters

Mammoth #	Vertical Capacity	Choker Capacity	Basket Capacities			Size (Width)	Approximate Weight Per Foot
			45 Degrees	60 Degrees	90 Degrees		
M10	10,000	8,000	7,070	8,660	20,000	3"	0.50
M20	20,000	16,000	14,140	17,320	40,000	3"	0.60
M30	30,000	24,000	21,210	25,980	60,000	4"	0.75
M40	40,000	32,000	28,280	34,640	80,000	4"	1.00
M50	50,000	40,000	35,350	43,300	100,000	6"	1.20
M60	60,000	48,000	42,420	51,960	120,000	6"	1.30
M70	70,000	56,000	49,490	60,620	140,000	6"	1.40
M80	80,000	64,000	56,560	69,280	160,000	6"	1.50
M90	90,000	72,000	63,630	77,940	180,000	8"	1.75
M100	100,000	80,000	70,700	86,600	200,000	8"	2.00
M125	125,000	100,000	88,375	108,250	250,000	8"	2.50
M150	150,000	120,000	106,050	129,900	300,000	8"	2.75
M175	175,000	140,000	123,725	151,550	350,000	8"	3.25
M200	200,000	160,000	141,400	173,200	400,000	10"	3.50
M225	225,000	180,000	159,075	194,850	450,000	10"	3.75
M250	250,000	200,000	176,750	216,500	500,000	10"	4.25
M275	275,000	220,000	194,425	238,150	550,000	12"	4.75
M300	300,000	240,000	212,100	259,800	600,000	12"	5.00
M350	350,000	280,000	247,450	303,100	700,000	12"	5.50
M400	400,000	320,000	282,800	346,400	800,000	14"	6.75
M450	450,000	360,000	318,150	389,700	900,000	14"	9.00
M500	500,000	400,000	353,500	433,000	1,000,000	14"	11.00

⚠ WARNING: Sling can fail if damaged, misused, or overloaded. Use only if trained. DEATH or INJURY can occur from improper use or care. Inspect before use and observe rated load to avoid death or personal injury. Avoid exposure to acid, alkali, and temperatures over 180 degrees. Pad edges of load to avoid damage to the sling.